

October 21st, 2025

Bosch Thermotechnology Corp
65 Grove Street
Watertown, MA 02472
dustin.gregoire@us.bosch.com
www.bosch-climate.us

Bosch Distributors,

Bosch is excited to announce the launch of our new 115V Modular Blower. Please see the below specification for more product-related details. This product is available for ordering and shipment effective October 21st, 2025.

PRODUCT DESCRIPTION

Bosch BMXF 115V Modular Blower, Multi-Position, ECM Motor

PRODUCT KEY FEATURES

BMXF 115V Modular Blower:

- 115V/120V
- 5-Speed high efficiency ECM Motor
- Removeable bottom for side or bottom return applications
- Multi-position installation (upflow, downflow, vertical, horizontal left-right)
- Reduces installation cost and time when replacing an AC and gas heating system with a heat pump solution by removing electric power installation barriers
- Industry standard furnace sizes for easy replacement



PRODUCT SPECIFICATION

October 2025

Page 2 of 5

	BMXFACTA	BMXFBCTA	BMXFCCTA	BMXFDCTA
Blower				
Diameter (in.)	10.984	10.984	10.984	10.984
Width (in.)	6.142	9.646	11.181	11.457
Fan Motor				
Horsepower (HP)	3/4	3/4	1	1
Maximum Operating Current (A)	19.3	9.3	12.3	12.3
Electrical Data				
Voltage-Phase-Hz	115/120-1Ph-60Hz	115/120-1Ph-60Hz	115/120-1Ph-60Hz	115/120-1Ph-60Hz
Minimum Circuit Ampacity ²	11.7	11.7	15.4	15.4
Max. Overcurrent Protection ³	20A	20A	25A	25A
Min / Max Volts	115V/120V			
Air Filter				
Air Filter Size (Side Return)	16" x 25"	16" x 25"	16" x 25"	16" x 25"
Air Filter Size (Bottom Return)	14" x 25"	16" x 25"	20" x 25"	24" x 25"
Weight				
Net Weight (without packaging) (lbs.)	86	92.5	106	112.5
Gross Weight (including packaging) (lbs.)	114.5	121	139	147.5
Dimensions				
Unit W x H x D (in.)	14-1/2*33-1/4*28-3/4	17-1/2*33-1/4*28-3/4	21*33-1/4*28-3/4	24-1/2*33-1/4*28-3/4
Unit W x H x D (in.) (With packaging)	17*40-3/8*31	20*40-3/8*31	23-9/16*40-3/8*31	27-1/6*40-3/8*31


AHRI 210/240 SYSTEM PERFORMANCE DATA

October 2025

Page 3 of 5

Outdoor Unit Model	Indoor Unit Model	Furnace Model	Cooling Capacity (BTU/h)			Heating Capacity			Cooling SCFM
	Coils/Air Handlers		Total	EER ²	SEER ²	Hi	HSPF ²	Low ⁴	
BOVA-36RTB-M20S	BMAC2430ABTA	BMXFACTA	23800	12.00	18.00	24000	9.00	19600	800/680
BOVA-36RTB-M20S	BMAC2430BBTA	BMXFBCTA	24000	12.00	18.50	24000	9.00	20000	800/680
BOVA-36RTB-M20S	BMAC3036ABTA	BMXFACTA	32800	10.60	16.00	34000	9.00	25000	1050/880
BOVA-36RTB-M20S	BMAC3036BBTA	BMXFBCTA	33600	11.00	16.50	34200	9.00	25000	1110/950
BOVA-36RTB-M20S	BMAC3036CBTA	BMXFCCTA	33600	11.00	16.50	34200	9.00	25000	1250/1100
BOVA-36RTB-M20S	BMAC4248BBTA	BMXFBCTA	33000	11.00	17.50	34200	9.00	25200	1150/980
BOVA-36RTB-M20S	BMAC4248CBTA	BMXFCCTA	33000	11.70	17.50	34200	9.00	25600	1220/1140
BOVA-60RTB-M20S	BMAC4248BBTA	BMXFBCTA	42500	11.70	16.00	43500	8.80	35000	1150/1000
BOVA-60RTB-M20S	BMAC4248CBTA	BMXFCCTA	44000	11.70	16.50	46500	8.80	35600	1470/1270
BOVA-60RTB-M20S	BMAC4248DBTA	BMXFDCTA	44500	11.70	16.50	47000	9.00	35600	1520/1320
BOVA-60RTB-M20S	BMAC4860CBTA	BMXFCCTA	51500	11.40	17.50	53500	8.50	38000	1460/1270
BOVA-60RTB-M20S	BMAC4860DBTA	BMXFDCTA	51500	11.70	18.00	54000	8.50	38500	1630/1380
BOVA-24RXB-M15S	BMAC2430ABTA	BMXFACTA	23600	10.60	16.00	24000	8.50	17600	800/680
BOVA-24RXB-M15S	BMAC2430BBTA	BMXFBCTA	24000	10.60	16.00	24000	8.50	17600	800/680
BOVA-24RXB-M15S	BMAC3036BBTA	BMXFBCTA	24000	10.60	16.00	24000	8.50	17600	800/680
BOVA-36RXB-M15S	BMAC3036ABTA	BMXFACTA	32000	10.00	16.00	34200	8.50	22800	980/850
BOVA-36RXB-M15S	BMAC3036BBTA	BMXFBCTA	32000	10.50	16.00	34200	8.50	23000	1020/880
BOVA-36RXB-M15S	BMAC3036CBTA	BMXFCCTA	32800	10.50	15.20	34200	8.50	23000	1200/1100
BOVA-36RXB-M15S	BMAC4248BBTA	BMXFBCTA	33600	10.20	16.00	33800	8.50	23000	1060/900
BOVA-36RXB-M15S	BMAC4248CBTA	BMXFCCTA	33000	10.20	15.20	34200	8.50	23000	1200/1140
BOVA-60RXB-M15S	BMAC4248BBTA	BMXFBCTA	42000	10.50	16.00	43000	8.50	33000	1150/980
BOVA-60RXB-M15S	BMAC4248CBTA	BMXFCCTA	44500	10.50	16.00	47000	8.50	34000	1470/1250
BOVA-60RXB-M15S	BMAC4248DBTA	BMXFDCTA	45500	10.50	16.00	47000	8.50	34200	1520/1300
BOVA-60RXB-M15S	BMAC4860CBTA	BMXFCCTA	53000	10.00	16.00	53500	8.50	37600	1510/1300
BOVA-60RXB-M15S	BMAC4860DBTA	BMXFDCTA	53500	10.00	16.00	54000	8.50	37600	1460/1270

¹ Seasonal Energy Efficiency Ratio; Certified per AHRI 210/240² Energy Efficiency Ratio; Certified per AHRI 210/240³ HSPF = Heating Seasonal Performance Factor; Certified per AHRI 210/240

*Blue shading indicates qualification for Energy Star and Energy Star Cold Climate v6.1

**Green shading indicates qualification for only Energy Star Cold Climate v6.1

**WARRANTY TERMS****Residential Limited Warranty*

October 2025

Page 4 of 5

Item	Terms
Compressors and internal components	10 years
Labor	90 days if REGISTERED

For Products installed in a one or two family residential dwelling BTC warrants that all compressors and internal components incorporated into the Product at the time of shipment by BTC shall remain free from defects in workmanship and materials for ten (10) years from the Commencement Date as defined below:

- i. For Products installed in newly constructed homes: date of home purchase by homeowner from builder.
- ii. For Products installed in existing residences: original date of installation.
- iii. If the above two cases cannot be verified: 90 days from the date of manufacture (as designated by the serial number on the unit).

If BTC determines that the Heat Pump or any part of the Heat Pump has a defect in workmanship or materials, BTC, at its option, will repair or replace the defective part.

Residential Labor – IF YOU REGISTER

If the Warranty Registration process has been completed and BTC determines that the Product or any part of the Product has a defect in workmanship or materials, BTC shall pay labor charges associated with the repair or replacement of the part in accordance with the Warranty Labor Allowance Schedule* for the period of ninety (90) days from the Commencement Date.

*Warranty Labor Allowance Schedule details are available on
www.boschprohvac.com

*Commercial Limited Warranty*

October 2025

Page 5 of 5

Item	Terms
Compressors and internal components	3 years

For Products installed in a building other than a one or two family residential dwelling, BTC warrants that all compressors incorporated into the Product at the time of shipment by BTC shall remain free from defects in workmanship and materials for three (3) years and other internal components incorporated into the Product components for one year from the shorter of from the Commencement Date.

If BTC determines that the Heat Pump or any part of the Heat Pump has a defect in workmanship or materials, BTC, at its option, will repair or replace the defective part.

***Note: Please refer to www.bosch-climate.us for full warranty terms and conditions.**

PRICING

Part Number	Model Number	Description	List Price
8-733-982-442	BMXFACTA	Modular Blower 115V, A Cabinet	\$ 2,303
8-733-982-443	BMXFBCTA	Modular Blower 115V, B Cabinet	\$ 2,392
8-733-982-444	BMXFCCTA	Modular Blower 115V, C Cabinet	\$ 2,590
8-733-982-445	BMXFDCTA	Modular Blower 115V, D Cabinet	\$ 2,738

Best Regards

Dustin Gregoire
Director of Sales Bosch & Key Accounts